



- Ready queue is partitioned into separate queues: foreground (interactive) background (batch)
- Each queue has its own scheduling algorithm
 - foreground RR
 - background FCFS
- Scheduling must be done between the queues
 - Fixed priority scheduling; (i.e., serve all from foreground then from background). Possibility of starvation.
 - Time slice each queue gets a certain amount of CPU time which it can schedule amongst its processes; i.e., 80% to foreground in RR, 20% to background in FCFS



Multilevel Feedback Queue

- A process can move between the various queues; aging can be implemented this way
- Multilevel-feedback-queue scheduler defined by the following parameters:
 - number of queues
 - scheduling algorithms for each queue
 - method used to determine when to upgrade a process
 - method used to determine when to demote a process
 - method used to determine which queue a process will enter when that process needs service

Example of Multilevel Feedback Queue

- Three queues:
 - Q_0 RR with time quantum 8 milliseconds
 - Q_1 RR time quantum 16 milliseconds
 - Q2 FCFS
- Scheduling
 - A new job enters queue Q_0 which is served FCFS. When it gains CPU, job receives 8 milliseconds. If it does not finish in 8 milliseconds, job is moved to queue Q_1 .
 - At Q₁ job is again served FCFS and receives 16 additional milliseconds. If it still does not complete, it is preempted and moved to queue Q₂.

3



Determining Length of Next CPU Burst

- Can only estimate the length
- Can be done by using the length of previous CPU bursts, using exponential averaging

$$\tau_{n+1} = \alpha t_n + (1 - \alpha) \tau_n$$

1. t_n = actual lenght of n^{th} CPU burst

- 2. τ_{n+1} = predicted value for the next CPU burst
- 3. $\alpha, 0 \leq \alpha \leq 1$

4. Define :



Exercise

Consider the exponential average formula used to predict the length of the next CPU burst. What are the implications of assigning the following values to the parameters used by the algorithm?

- a. $\alpha = 0$ and $\tau_0 = 100$ milliseconds
- b. $\alpha = 0.99$ and $\tau_0 = 10$ milliseconds

Answer: When $\alpha = 0$ and $\tau_0 = 100$ milliseconds, the formula always makes a prediction of 100 milliseconds for the next CPU burst. When $\alpha =$ 0.99 and $\tau_0 = 10$ milliseconds, the most recent behavior of the process is given much higher weight than the past history associated with the process. Consequently, the scheduling algorithm is almost memory-less, and simply predicts the length of the previous burst for the next quantum of CPU execution.



8















Transition from User to Kernel Mode

- How to prevent user program getting stuck in an infinite loop / process hogging resources
 - \rightarrow Timer: Set interrupt after specific period (1ms to 1sec)
 - Operating system decrements counter
 - When counter zero generate an interrupt
 - Set up before scheduling process to regain control or terminate program that exceeds allotted time



Standard C Library Example

 C program invoking printf() library call, which calls write() system call







Virtual Machines

- A virtual machine takes the layered approach to its logical conclusion. It treats hardware and the operating system kernel as though they were all hardware
- A virtual machine provides an interface *identical* to the underlying bare hardware
- The virtual machine creates the illusion of multiple processes, each executing on its own processor with its own (virtual) memory





Virtual Machines (Cont.)

- The virtual-machine concept provides complete protection of system resources since each virtual machine is isolated from all other virtual machines. This isolation, however, permits no direct sharing of resources.
- A virtual-machine system is a perfect vehicle for operating-systems research and development. System development is done on the virtual machine, instead of on a physical machine and so does not disrupt normal system operation.
- The virtual machine concept is difficult to implement due to the effort required to provide an *exact* duplicate to the underlying machine

26

VMware Architecture application application application application guest operating system guest operating guest operating system (free BSD) (Windows NT) (Windows XP) virtual CPU virtual memory virtual devices virtual CPU virtual memory virtual devices virtual CPU virtual memory virtual devices virtualization layer host operating system (Linux) hardware CPU I/O devices memory 27



Acknowledgements

- "Operating Systems Concepts" book and supplementary material by A. Silberschatz, P. Galvin and G. Gagne
- "Operating Systems: Internals and Design Principles" book and supplementary material by W. Stallings
- "Modern Operating Systems" book and supplementary material by A. Tanenbaum
- R. Doursat and M. Yuksel from UNR